




TECHNICAL DATA SHEET
FLOORPAN
 URBAN

8 MM - CLASS 32 - AC4

THICKNESS	mm	8	EN 13329+A1	
WIDTH	mm	197	EN 13329+A1	
LENGHT	mm	1205	EN 13329+A1	
SURFACE		Authentic		
EUROPEAN STANDARD	-	  	EN13329	
PACKAGE THE DETAILS				
PIECE	8 piece / 1 package			
M ²	1,899 m ²			
KG	13,9 kg			
PALLET THE DETAILS				
PIECE	60 package / 1 pallet			
M ²	113,94 m ²			
KG	840 kg			
CLASS	-	32	EN 13329+A1	
ABRASION RESISTANCE	-	AC4	EN 13329+A1	
THICKNESS SWELLING	%	≤18	ISO 24336	
RESISTANCE TO IMPACT	SMALL BALL	N	≥12	EN 13329+A1
	LARGE BALL	mm	≥750	EN 13329+A1
WARRANTY DOMESTIC / COMMERCIAL	Years	15/10	-	
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438	
SURCAFE SOUNDNESS	N/mm ²	≥1.25	EN 13329+A1	
LOCK STRENGTH	LENGHT	kN/m	f10,2 ≥ 1	ISO 24334
	WIDTH	kN/m	fs0,2 ≥ 2	
EFFECT OF A CASTOR CHAIR	25,000 Cycles	No Damage	EN 425:2002	
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424	
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1	
HEIGHT DIFFIRENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1	
MOISTURE CONTENT	%	4-10	EN 322	
FIRE RESISTANCE	Class	C _s 1	EN 9239-1	
FORMALDEHYDE EMISSION	mg/m ² h	≤3,5 (E1)	EN 12460-3	
SLIP RESISTANCE	Class	35<Rd<45 Class 2	EN 14041:2008	
THERMAL CONDUCTIVITY	W/(m*K)	0.148	EN 12667:2001	
SOUND RATING	dB	ΔLw=14 C _i Δ,-9 L _{n,w} =64 C _{i,r} =-2 L _{n,0,w} =78 C _i =-1	ISO 717-2	

